




# From last meetings: SPACAL design implementation in Geant4

- Enabled with new branch 2DSpacal:
  - In nightly build, but not used by default
    - https://github.com/sPHENIX-Collaboration/macros/pull/2
    - https://github.com/sPHENIX-Collaboration/coresoftware/pull/19
  - Activated with this flag in Fun4All\_sPHENIX.C

```
Cemc_spacal_configuration =
PHG4CylinderGeom_Spacalv1::k2DProjectiveSpacal;
```





#### Towers project towards IP



### Stainless steel SS310 Support box



#### Gap between modules are also implemented

- 300um tolerance outside super modules skins
- ~2mil between SPACAL and SS skin.
- ~2mil between SPACAL modules

2x2 2D tapered SPACAL modules

in Huang <jihuang@bnl.gov>

Simulation Meeting

### Recent updates

- Chris produced first few test productions:
  - /gpfs02/phenix/prod/sPHENIX/preCDR/pro.1-beta.2/spacal1d
  - /gpfs02/phenix/prod/sPHENIX/preCDR/pro.1-beta.2/spacal2d
- Implementation of analyzing Geant4 data in tower structures as built:
  - Tag hits in SPACAL output with sector/tower/fiber IDs.
  - Add a cell builder to group hit in each 10M SPACAL fiber separately in each cell (which allow us to implement fiber-fiber light collection eff. when needed)
  - Update tower builder to take SPACAL cells and collection light yield from each cell.
- Submitted to use in production: <u>https://github.com/sPHENIX-</u> <u>Collaboration/coresoftware/pull/29</u>




### Test beam comparison 1

- One of the long last concern is lack of beam test calibration for our simulation
- Obtained eRD1 2014 beam test geometry and data with many help from Oleg Tsai, Alex Kiselev and Craig Woody
- Implemented in Geant4

SPACAL prototypes in 2014 Fermilab beam test






Courtesy: O. Tsai (UCLA)



# Test beam comparison 2: 8 GeV electron shower in Geant4

Implementation in Geant4 relatively straightforward with the new engineering based setup




Side view (non-tapered side)
~= Z vs R view


Side view (tapered side) = beam axis view



### Test beam comparison 3: More detailed views of fiber matrix



# Test beam comparison 4: 8 GeV electron shower in Geant4 VS data



Full Geant4 sim QGSP\_BERT\_HP + light yield model (Geant4 default Birk)
Not yet applied: SiPM noise, photon fluctuation, fiber/fiber response



#### Photon analysis and Clusterizer choice

- Discussed possible photon Clusterizer with Stefan Bathe and Megan Connors
- Fast pre-CDR solution for photon performance in HI
  - Trying Sasha's PHENIX clusterizer
  - Ideal clustering (group tower around truth photon track)
  - Try FastJet with R = Mollie radius?
- Long term, construct an official pacakge?
  - CMS island algorithm (Thanks to Stefan and Yen-Jie Lee (MIT)): <a href="https://cds.cern.ch/record/687345/files/note01">https://cds.cern.ch/record/687345/files/note01</a> 034.pdf
  - Alice algorithm
  - General purpose package?
  - More volunteers?



### **Pre-CDR plots**

- Single particle (e/mu/pi/p/gamma/pi0)
  - Line shapes [Jin]
     need to finish test beam setup
  - Linearity [Jin]
     need new production with towering
  - Energy resolution [Jin] <- need new production with towering</li>
  - Sampling fraction [Jin]<- ready to produce plot with test production</li>
  - Dynamic range [Jin] <- need new production with towering</li>
- Au+Au HIJING embedded
  - Underlying event energy and fluctuation [Jin]
     need new production with towering
  - Rejection vs efficiency for electrons [Jin]
     need new production, verify track proj. tools
  - Photon resolution [Stefan and Megan]
    - <- need new production, decide the clusterizer
- ▶ EM energy trigger performance
  - Turn-on curve [Jin] <- need new production, improve last tools</li>

